



# Material Safety Data Sheet

## KwikSeal 35

### Component A

**MANUFACTURER**  
Elastomer Specialties, Inc.  
2210 South Highway 69  
Wagoner, OK 74467  
(918) 485-2835

Issued: August 2000  
Revised: November 2005 – new address  
Revised: July 2009

### 1 - Chemical Product Identification

Product Code:	1208
Product Name	KwikSeal 35 <b>Component A</b>
Chemical Family	Aromatic Isocyanate Prepolymer
Chemical Name	Diphenylmethane Diisocyanate (MDI) Prepolymer
Synonyms	Modified Diphenylmethane Diisocyanate (MDI)
CAS Number	39420-98-9
Formula	Not applicable

### 2 - Composition / Information on Ingredients - HAZARDOUS INGREDIENTS

INGREDIENT NAME/CAS #	EXPOSURE LIMITS	CONCENTRATION
4,4' - Diphenylmethane Diisocyanate (MDI) 101-68-8	OSHA: .02 ppm Ceiling .20 mg/m <sup>3</sup> Ceiling ACGIH: .005 ppm TWA .051 mg/m <sup>3</sup> TWA	Less than 15%
2,4' - Diphenylmethane Diisocyanate (MDI) 5873-54-1	OSHA: Not Established ACGIH: Not Established	Less than 10%
2,2' - Diphenylmethane Diisocyanate (MDI) 2536-05-2	OSHA: Not Established ACGIH: Not Established	Less than 2%

### 3 - Composition / Information on Ingredients - OTHER INGREDIENTS

INGREDIENT NAME/CAS #	EXPOSURE LIMITS	CONCENTRATION
Polyurethane Prepolymer 39420-98-9	OSHA: Not Established ACGIH: Not Established	Less than 80%

### 4 - Hazards Identification

**Emergency Overview:** Warning!  
Color: Colorless to Straw Yellow;  
Form: Liquid;  
Odor: Slightly musty odor; May cause eye, skin, and respiratory tract irritation;  
Harmful if inhaled; May cause allergic respiratory reaction;  
May cause allergic skin reaction; Toxic gases/fumes are given off during burning or thermal decomposition.

#### POTENTIAL HEALTH EFFECTS:

##### ROUTE (S) OF ENTRY

Skin Contact from liquid and aerosols (spray application).

Inhalation: Although MDI is low in volatility, an inhalation hazard can exist from MDI aerosols or vapors formed during heating, foaming or spraying.

#### HUMAN EFFECTS AND SYMPTOMS OF OVER-EXPOSURE:

**ACUTE INHALATION:** MDI vapors or mist at concentrations above the TLV can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). Persons with a pre-existing, nonspecific bronchial hyper-reactivity can respond to concentrations below the TLV with similar symptoms as well

nonspecific bronchial hyper-reactivity can respond to concentrations below the TLV with similar symptoms as well as asthma attack. Exposure well above the TLV may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). These effects are usually reversible. Chemical or hypersensitive pneumonitis, with flu-like symptoms (e.g., fever, chills) has also been reported. These symptoms can be delayed up to several hours after exposure.

**CHRONIC INHALATION:** As a result of previous repeated overexposures or a single large dose, certain individuals develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure). Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air or other irritants. This increased lung sensitivity can be reported to cause lung damage (including decrease in lung function) which may be permanent. Sensitization can either be temporary or permanent.

**ACUTE SKIN CONTACT:** Isocyanates react with skin protein and moisture and can cause irritation which may include the following symptoms: reddening, swelling, rash, scaling or blistering. Cured material is difficult to remove.

**CHRONIC SKIN CONTACT:** Prolonged contact can cause reddening, swelling, rash, scaling, blistering, and in some cases, skin sensitization. Individuals who have skin sensitization can develop these symptoms from contact with liquid or vapors. Animal tests have indicated that respiratory sensitization can result from skin contact with MDI. This data reinforces the need to prevent direct skin contact with MDI. (See *Toxicological Information, Sensitization*.)

**ACUTE EYE CONTACT:** Liquid, aerosols or vapors are irritating and can cause tearing, reddening and swelling. If left untreated, corneal damage can occur and injury is slow to heal. However, damage is usually reversible. See First Aid Measures for treatment.

**CHRONIC EYE CONTACT:** None found.

**ACUTE INGESTION:** Can result in irritation and corrosive action in the mouth, stomach tissue and digestive tract. Symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea.

**CHRONIC INGESTION:** None found.

**CARCINOGENICITY:** Neither MDI nor polymeric MDI are listed by the NTP, IARC or regulated by OSHA as carcinogens.

NTP— - - - - Not listed

IARC— - - - - Not listed

OSHA— - - - - Not regulated

OTHER— - - - See results of two year inhalation study in Toxicological Information, CARCINOGENICITY.

**MEDICAL CONDITIONS:** Aggravated by Exposure: Asthma, other respiratory disorders (bronchitis, emphysema, bronchial hyper-reactivity), skin allergies, eczema.

## 5 - First Aid Measures

**FIRST AID FOR EYES:** Flush with copious amount of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Refer individual to physician or ophthalmologist for immediate follow-up.

**FIRST AID FOR SKIN:** Remove contaminated clothing. Wash affected skin thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse. For severe exposures, get under safety shower after removing clothing, then get medical attention. For lesser exposures, seek medical attention if irritation develops or persists after the area is washed.

**FIRST AID FOR INHALATION:** Move to an area free from risk of further exposure. Administer oxygen or artificial respiration as needed. Obtain medical attention. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Consult physician should this occur.

**FIRST AID FOR INGESTION:** **DO NOT INDUCE VOMITING.** Give 1 to 2 cups of milk or water to drink. **DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.** Consult a physician.

**NOTE TO PHYSICIAN:**

Eyes. Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation frequently. Workplace vapors have produced reversible corneal epithelial edema impairing vision.

Skin. This compound is a known skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burns. If burned, treat as thermal burn.

Ingestion. Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound.

Respiratory. This compound is a known pulmonary sensitizer. Treatment is essentially symptomatic. An individual having a known or suspected pulmonary sensitization reaction to this material should be removed from exposure to any isocyanate.

Issue Date: August 2000

Revised: November 2005

Revised: July 2009

## 6 - Fire Fighting Measures

FLASH POINT: 421.0 F (216.1 C) Pensky-Martens Closed Cup (ASTM D-93)

EXTINGUISHING MEDIA: Dry chemical—Carbon Dioxide; Foam; Water spray for large fires.

SPECIAL FIRE FIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by firefighters. During a fire, MDI vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. (See Stability and Reactivity). At temperatures greater than 400°F (204°C), polymeric MDI can polymerize and decompose which can cause pressure build-up in closed containers. Explosive rupture is possible. Therefore, use cold water to cool fire-exposed containers.

## 7 - Accidental Release Measures

SPILL OR LEAK PROCEDURES: Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment, including respiratory equipment during clean-up. (See Employee Protection Recommendations).

Major Spill: Call CHEMTREC at 800.424.9300. If transportation spill, call CHEMTREC @ 800.424.9300. If temporary control of isocyanate vapor is required, a blanket of protein foam (available at most fire departments) may be placed over the spill. Large quantities may be pumped into closed, but not sealed, container for disposal.

Minor Spill: Absorb isocyanates with sawdust or other absorbent, shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%), or water (90%), concentrated ammonia (3-8%) and detergent (2%). Add about 10 parts of neutralizer per part of isocyanate, with mixing. Allow to stand uncovered for 48 hours to let CO<sub>2</sub> escape.

Clean-up: Decontaminate floor with decontamination solution letting stand for at least 15 minutes.

## 8 - Handling and Storage

STORAGE TEMPERATURE (MIN/MAX): 60°F (15°C) /95°F (35°C)

SHELF LIFE: 6 months @ 77°F (25°C)

SPECIAL SENSITIVITY: If container is exposed to high heat, 400°F (204°C) it can be pressurized and possibly rupture. MDI reacts slowly with water to form CO<sub>2</sub> gas. This gas can cause sealed containers to expand and possibly rupture.

HANDLING/STORAGE PRECAUTIONS: Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Avoid contact with skin and eyes. Do not breathe aerosols or vapors. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent chronic over-exposure from inhalation. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Exposure to vapors of heated MDI can be extremely dangerous. Employee education and training in the safe use and handling of this compound are required under the OSHA Hazard Communication Standard.

## 9 - Personal Protection

EYE PROTECTION REQUIREMENTS: Liquid chemical goggles. Vapor resistant goggles should be worn when contact lenses are in use. In a splash hazard environment chemical goggles should be used in combination with a full face shield.

SKIN PROTECTION REQUIREMENTS: Permeation resistant gloves (butyl rubber, nitrile rubber, polyvinyl alcohol). However, please note that PVA degrades in water. Cover as much of the exposed skin area as possible with appropriate clothing. If skin creams are used, keep the area covered by the cream to a minimum.

VENTILATION REQUIREMENTS: Local exhaust should be used to maintain levels below the TLV whenever MDI is processed, heated or spray applied. Standard reference sources regarding industrial ventilation (i.e., ACGIH Industrial Ventilation) should be consulted for guidance about adequate ventilation.

RESPIRATOR REQUIREMENTS: Concentrations greater than the TLV can occur when MDI is sprayed, heated or used in a poorly ventilated area. In such cases, or whenever concentrations of MDI exceed the TLV or are not known, respiratory protection must be worn. A supplied air respirator (either positive pressure or continuous flow type) is required. In an emergency situation, a self-contained breathing apparatus may be used. MDI has poor warning properties since the concentration at which MDI can be smelled is substantially higher than the maximum exposure limit. Observe OSHA regulations for respirator use (29 FR 1910.134).

MONITORING: Isocyanate exposure levels must be monitored. Monitoring of airborne isocyanate in the breathing zone of individuals should become part of the overall employee exposure characterization program. Monitoring techniques have been developed by NIOSH and OSHA. Upon request, Bayer Corporation can make available methods which are modifications of these NIOSH and OSHA methods.

Issue Date: August 2000  
Revised: November 2005  
Revised: July 2009

**MEDICAL SURVEILLANCE:** Medical supervision of all employees who handle or come in contact with isocyanates is recommended. These should include pre-employment and periodic medical examinations with pulmonary function tests (FEV, FVC as a minimum). Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases or recurrent skin eczema or sensitization should be excluded from working with isocyanates. Once a person is diagnosed as sensitized to an isocyanate, no further exposure can be permitted.

**ADDITIONAL PROTECTIVE MEASURES:** Safety showers and eyewash stations should be available. Educate and train employees in safe use of product. Follow all label instructions. For additional information, contact Bayer Corporation.

## 10 - Physical and Chemical Properties

PHYSICAL FORM	Liquid
COLOR	Colorless to Straw Yellow
ODOR	Slightly musty odor
ODOR THRESHOLD	Not established
pH	Not applicable
BOILING POINT	406°F (208°C) @ 5 mmHg for MDI
MELTING/FREEZING POINT	Range 50°F (10°C) for MDI to 60°F (16°C)
VISCOSITY	Not applicable
SOLUBILITY IN WATER	Not soluble. Reacts slowly with water to liberate CO <sub>2</sub> gas
SPECIFIC GRAVITY	1.090 @ 77°F (93°C)
BULK DENSITY	9.10 lbs/gal
% VOLATILE BY VOLUME	Negligible
VAPOR PRESSURE	Less than 10-5 mmHg @ 77°F (25°C) for MDI
VAPOR DENSITY	8.5 (MDI) (Air = 1)

## 11 - Stability and Reactivity

**STABILITY:** This is a stable material

**HAZARDOUS POLYMERIZATION:** May occur; Contact with moisture, other materials which react with isocyanates, or temperatures above 400°F (204°C), may cause polymerization.

**INCOMPATIBILITIES:** Water, amines, strong bases, alcohols. Will cause some corrosion to copper alloys and aluminum.

**INSTABILITY CONDITIONS:** Contamination with water.

**DECOMPOSITION PRODUCTS:** By high heat and fire: carbon monoxide, oxides of nitrogen, traces of HCN, MDI vapors or aerosols.

## 12 - Toxicological Information

**TOXICITY DATA FOR:** Diphenylmethane Diisocyanate (Monomeric and Polymeric)

**ACUTE TOXICITY:**

Oral LD50 Greater than 15,800 mg/kg (Rat)

Dermal LD50 Greater 5010 but less than 7,940 mg/kg (Rabbit)

Inhalation LC50 The 4 hour LC50 for polymeric MDI in rats ranges from 370 to 490 mg/m<sup>3</sup>.

The LC50 for monomeric MDI was estimated to be between 172 and 187 mg/m<sup>3</sup>.

**Eye Effects:** Slight to moderate irritation.

**Skin Effects:** Slight to moderate irritation.

**Sensitization:** MDI has been shown to produce dermal sensitization in laboratory animals. Evidence of respiratory sensitization has also been observed in guinea pigs. In addition, there is some evidence suggestive of cross sensitization between different types of diisocyanates.

**Chronic Toxicity:** In a combined chronic inhalation toxicity/oncogenicity study, rats were exposed to an aerosol of polymeric MDI for 6 Hours per day, 5 days per week for one or two years. The exposure concentrations were 0, 0.2, 1.0, and 6.0 mg/m<sup>3</sup>. Microscopic examination of tissues revealed the effects of irritation to the nasal cavity and lungs in animals exposed to 1.0 and 6.0 mg/m<sup>3</sup>. The No Observable Effect Level (NOEL) was 0.2 mg/m<sup>3</sup>.

**Carcinogenicity:** In the study described above (See Chronic Toxicity), the occurrence of pulmonary adenomas and a single pulmonary Aden carcinoma was considered to be related to MDI. These tumors were observed only in rats exposed to the high concentration of 6.0 mg/m<sup>3</sup>.

**Mutagenicity:** Positive (Salmonella microsome test with metabolic activation; cell transformation assay) as well as negative (mouse lymphoma specific locus mutation test with or without metabolic activation) results have been observed "in vitro". However, MDI was negative in an "in vivo" (mouse micronucleus) assay.

**Developmental Toxicity:** Rats were exposed to polymeric MDI at air concentrations of 0, 1, 4, and 12 mg/m<sup>3</sup> during days 6 - 15 of gestation. Maternal Toxicity (including mortality) was observed at the highest concentration of 12 mg/m<sup>3</sup> accompanied by embryo and fetal toxicity. However, no teratogenic effects were observed even at this lethal concentration.

Issue Date: August 2000

Revised: July 2009

**13 - Ecological Information**

ECOLOGY DATA FOR: Diphenylmethane Diisocyanate (Monomeric and Polymeric)

Aquatic Toxicity: LC50 - 24 hour (static): Greater than 500 mg/liter for Daphnia magna, Limnea Stagnalis, and Zebra fish (Brachydanio rerio) for both polymeric and monomeric MDI.

**14 - Disposal Considerations**

WASTE DISPOSAL METHOD: Waste must be disposed of in accordance with federal, state, and local environmental control regulations. Incineration is the preferred method.

EMPTY CONTAINER PRECAUTIONS: Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Empty decontaminated containers should be crushed to prevent reuse. DO NOT HEAT OR CUT EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH. (See Fire Fighting Measures and Stability & Reactivity). Gases may be highly toxic.

TRANSPORTATION EMERGENCIES: Elastomer Specialties requires that CHEMTREC be immediately notified (800.424-9300) when this product is unintentionally released from its container during its course of distribution, regardless of the amount released. Distribution includes transportation, storage incidental to transportation, loading and unloading. Such notification must be immediate and made by the person having knowledge of the release.

**15 - Transportation Information**

TECHNICAL SHIPPING NAME	Methylene diphenyl diisocyanate
FREIGHT CLASS BULK	Methylene diphenyl diisocyanate
FREIGHT CLASS PACKAGE	Chemical, NOI (Isocyanate), NMFC 60000
PRODUCT LABEL	Product Label Established

**DOT (Domestic Surface)**

PROPER SHIPPING NAME	Other Regulated Substances, Liquid, N.O.S. * SEE NOTE BELOW
HAZARD CLASS OR DIVISION	9
UN/NA NUMBER	NA3082
PACKAGING GROUP	PG III
HAZARDOUS SUBSTANCE	MDI, (Methylene diphenyl diisocyanate
DOT PRODUCT RQ lbs (kgs)	33333 lbs (15119.8 kgs)
HAZARD LABEL (s)	Class 9
HAZARD PLACARD(s)	Class 9

\* When in individual containers of less than the product RQ, this material ships as non-regulated.

<b>IMO / IMDG code (Ocean):</b>	HAZARD CLASS DIVISION NUMBER	Non-Regulated
<b>ICAO / IATA (Air):</b>	HAZARD CLASS DIVISION NUMBER	Non-Regulated

HARMONIZED SYSTEM TARIFF #: **HS# 3909.50.5000**

**16 - Regulatory Information**

OSHA STATUS: This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA STATUS: On TSCA Inventory

CERCLA REPORTABLE QUANTITY: 5000 LBS FOR 4,4' - Diphenylmethane Diisocyanate, CAS# 101-68-8.

SARA TITLE III:

SECTION 302: EXTREMELYHAZARDOUS SUBSTANCES: None

SECTION 311/312: HAZARD CATEGORIES: Immediate Health Hazard; Delayed Health Hazard; Reactive Hazard.

SECTION 313: TOXIC CHEMICALS: 4,4' - Diphenylmethane Diisocyanate, CAS# 101-68-8; Upper Bound 15%

RCRA STATUS: MDI is not listed as a hazardous waste. To the best of our knowledge, MDI does not meet the criteria of a hazardous waste if discarded in its purchased form. However, under RCRA, it is the responsibility of the user of products to determine, at the time of disposal, whether a product meets any of the criteria for a hazardous waste. This is because product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics under the new Toxicity Characteristics Leaching Procedure (TCLP) 40 Code of Federal Regulations 261.20-24. The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

Issue Date: August 2000  
Revised: November 2005  
Revised: July 2009

<u>COMPONENT NAME</u> <u>/CAS NUMBER</u>	<u>CONCENTRATION</u>	<u>STATE CODE</u>
4,4' -Diphenylmethane Diisocyanate (MDI) 101-68-8	Less than 15%	RI, NJ1, NJ4, CN2 PA1, FL, IL, MA, PA3, NJ4
2,4' - Diphenylmethane Diisocyanate (MDI) 5873-54-1	Less than 10%	PA3, NJ4
2,2' - Diphenylmethane Diisocyanate (MDI) 2563-05-2	Less than 2%	NJ4
Polyurethane Prepolymer 39420-98-9	Less than 80%	PA3, NJ4

FL = Florida Substance List

IL = Illinois Toxic Substances List

MA = Massachusetts Hazardous Substance List

NJ1 = New Jersey Hazardous Substance List

NJ4 = New Jersey Other—included in 5 predominant ingredients > 1%

PA1 = Pennsylvania Hazardous Substance List

PA3 = Pennsylvania Non-hazardous present at 3% or greater.

RI = Rhode Island List of Designated Substances

CN2 = Canada WHMIS Ingredient Disclosure List over 0.1%.

#### CALIFORNIA PROPOSITION 65

To the best of our knowledge, this product contains no levels of listed substances, which the state of California has found to cause cancer, birth defects or other reproductive effects.

#### 17 - Other Information

##### NFPA 704M RATINGS:

Health	Flammability	Reactivity	Other
3	1	1	
0 = Insignificant	1 = Slight	2 = Moderate	3 = High
			4 = Extreme

##### HMIS RATINGS:

Health	Flammability	Reactivity
3*	1	1
0 = Minimal	1 = slight	2 = Moderate
4 = Severe		3 = Serious
	* = Chronic Health Hazard	

Elastomer Specialties' method of hazard communication is comprised of Product Labels and Material Safety Data Sheets. HMIS and NFPA ratings are provided by Elastomer Specialties, Inc. as a customer service.

***This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Elastomer Specialties, Inc. The data on this sheet relates only to the specific material designated herein. Elastomer Specialties, Inc. assumes no legal responsibility for use or reliance upon this data.***

Issue Date: August 2000  
Revised: November 2005  
Revised: July 2009