



## Technical Data

*IsoSolv*

Solvent / Cleaner  
NB 1299  
Revised: 041510

### MANUFACTURER

GatorHyde Protective Coatings, Inc.  
2210 South Highway 69  
Wagoner, OK 74467  
Phone: (918) 485-2835  
Fax: (918) 485-2856

### PRODUCT DESCRIPTION:

**IsoSolv** is a water soluble, dibasic ester based solvent containing no aromatics or petroleum distillates. **IsoSolv** is an environmentally friendly cleaner designed to provide maximum cleaning power for removing uncured polyurethane's, epoxies, polyester resins, and polyureas. **IsoSolv** is very effective in removing uncured deposits of isocyanate from plural component pumps, high and low pressure spray equipment, mixing tools, caulking guns or any other tool or equipment surface which requires cleaning.

### APPLICATION EQUIPMENT:

**IsoSolv** can be applied by brush, Low Pressure Hudson Sprayer, or by soaking the tool or equipment. Once part has been cleaned rinse thoroughly with water. **Note!** **When cleaning mixing tools make sure IsoSolv has been completely removed and neutralized before re-using tools.**

### ADVANTAGES:

**IsoSolv** is easy to use and should be applied similar to other solvents or cleaners, however because of the low evaporation rate, **IsoSolv** lasts much longer than most other solvent cleaners.

### PHYSICAL PROPERTIES:

VISCOSITY @ 25° C, cps	25
APPEARANCE	Clear Liquid
ODOR	Mild Sweet Odor
SPECIFIC GRAVITY @ 25° C	1.08
FLASH POINT	>200°F
VAPOR DENSITY (Air=1)	N.D.
EVAPORATION RATE (Water = 1)	<1

### SPECIAL PROTECTION INFORMATION:

When using **IsoSolv**, make sure adequate ventilation is available. It is advisable to use neoprene gloves when working with material. Safety glasses, chemical goggles or face shields are also recommended.

### SHELF LIFE & STORAGE:

One year in factory delivered, unopened containers. Store **IsoSolv** away from areas of high heat.

### SHIPPING INFORMATION:

**IsoSolv** is not R.C.R.A. or D.O.T. regulated which means it can safely and legally be transported and used in all 50 states.

### PACKAGING:

**IsoSolv** is available in 1 and 5 gallon polyethylene containers and 55 gallon drums.

### WARRANTY:

The technical data and any other printed information furnished by GatorHyde are true and accurate to the best of our knowledge. **IsoSolv** conforms to in-house quality control procedures and should be considered free of defects. Due to the wide range of applications of this product, it is impossible to assume responsibility for any errors in regard to application, coverage, usage, or injuries resulting from the use of this product. GatorHyde makes no warranty expressed or implied, of its products and shall not be liable for indirect or consequential damage in any event.